

NT-01b-02.A1

FLAT NON-TRAFFICABLE
INVERTED ROOF
SINGLE-LAYER APP WATERPROOFING
TEXLOSA

PARAPET WALL DETAIL:

- LOAD-BEARING SUPPORT
- 2. SLOPE FORMATION LAYER
- 3. BAND REINFORCEMENT:

MORTERPLAS SBS FP 3KG BAND 33

4. WATERPROOFING:

BASIC: SUPER MORTERPLAS 4 KG
IMPROVED: SUPER MORTERPLAS 4,8 KG

- 5. SEPARATION LAYER: ROOFTEX 300
- 6. INSULATING TILE: TEXLOSA R
- 7. BAND REINFORCEMENT:
 MORTERPLAS FV 4KG MIN
- 8. WALL FINISH



Texsa Systems s.l.u. C/ Ferro, 7 (Pol.Ind. Can Pelegri) 08755 Castellbisbal (Barcelona) Spain

> Tel. (+34) 93.635.14.00 Fax. (+34) 93.635.14.88 e-mail: texsa@texsa.com

Project

FLAT NON-TRAFFICABLE INVERTED ROOF -SINGLE-LAYER APP WATERPROOFING + TEXLOSA

Customer:

Object:

PARAPET WALL DETAIL

NT: Texsa is not responsibility for the solution.

This detail is only indicative and should be verified by the designer and / or the applicator according to the real job site conditions which must approve it under their own responsibility.

 Prot. n.
 Our. ref.

 RA

 Sist.code
 Data:
 Scale:

 NT-01b-02.A1
 01-2016
 NTS

DRAFT