

## **DECLARATION OF PERFORMANCES**

WPBSP241

LBA-15-PE

**APPLUS-LGAI** 

1. Number and/or identification code: **WPBSP241** 

2. Name, type, batch or serial number:

## **TEXSELF 1,5**

3. Intended uses:

Flexible sheets for waterproofing, underlays for discontinuous roofing.. Bitumen basement tanking sheets (Type T)

4. Name and conctact adress of the manufacturer: **TEXSA SYSTEMS SLU - C/ Ferro, 7 - Pol. Can Pelegrí - 08755 Castellbisbal - Barcelona (SPAIN)** 

5. System or systems of assessment and verification of constancy of performance: **System 2+** 

Task carried out:	System	Done / Issued:
Factory Production Control (FPC)	2+	AENOR - 0099
		on the basis of: 0099/CPR/A85/0087
Fire reaction	3	APPLUS-LGAI

3

## External fire behaviour

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Watertightness	Pass (60 kPa)	
Tensile properties:		
Maximum tensile strength (L x T) (N/50mm)	270 ± 70 270 ± 70	
Elongation (L x T) (%)	$250 \pm 50$ $220 \pm 50$	EN 13859-1:2010 EN 13969:2004
Tear strength (nail) (L x T) (N)	180 x 140 ± 50	
Flexibility at low temperature (°C)	≤ -15	
Fire reaction	E	
Joint shear resistance (L x T) (N/50mm)	270 x 270 ± 70	
Water penetration resistance	W1	EN 12050 1-2010
Durability (water penetration / tensile)	NPD	EN 13859-1:2010
Durability (Watertightness)	Pass (60 kPa)	EN 13969:2004
Impact resistance (mm)	NPD	
Watertightness durability against chemical agents	NPD	
Hazardous substances	NPD	

NE - Not relevant, NPD - No performance determined

The performance of the product identified in points 1 is in conformity with the declared performace in point 6. This declaration of performance is issued under the sole reponsability of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

J. Fiter RD& i Director

Castellbisbal, 01/06/2015